

OSS-ZSD-48/24 FIBRE OPTIC CLOSURE

FEATURES:

- designed for splicing customer drop cable fibres to the fibres of a distribution cable, dedicated for outdoor and indoor use
- the cover and base are made of high quality UV stabilised plastic with wide operating temperature range -40°C to +85°C
- hinged splice tray allows convenient fibre management, splitter and connectros installation
- divisible cable entry for the distribution cable loop through applications
- quick and easy installation on OSS-SZD-60 or OSS-SZD-80 cabel reserve frames with the use of the mounting plate

EQUIPMENT:

- splice protectors
- 2 lock keys
- cable ties
- fibre protection tubes
- installation kit

OPTIONAL EQUIPMENT:

- OSS-SZD-80 Access Aerial Cable Reserve Frame
- OSS-SZD-PL Mounting Plate

TECHNICAL SPECIFICATION:

	OSS-ZSD-48/24SC/2/24-A
application	indoor, outdoor, aerial
number of distribution cable entry	2
number of customer drop cable ports	24
distribution cable diameter range [mm]	5 to 16
customer drop cable diameter range [mm]	3 to 6
maximum splice capacity	48
number of adapter slots	24 SC adapters or 24 LC Duplex adapters
number of splitters in mini type housings	3 splittery PLC 1 x 8
dimensions length/width/height [mm]	390/250/140
cable to port sealing method	rubber seals
sheath material	PC + ABS
protection grade	IP68

ORDERING:

OSS-ZSD/48/24SC/2/24-A - OSS-ZSD-48/24 Fibre Optic Closure, 48 fibre splice capacity



*OSS-ZSD-48/24 Fibre Optic Closure
with installation kit*