

## PS-4 FIBRE OPTIC DISTRIBUTION FRAME



Fibre Optic Distribution Frame PS-4

### FEATURES:

- dedicated for installation in telecommunication central offices with limited space and high number of cables and connectors
- provides from 72 fibre terminations in PS-4/72 up to 336 in PS-4/320
- splice tray, outdoor cable excess length fibre and pigtail storage sections in the bottom part of the cabinet
- draw-out adapter frame for E2000 or SC adapter standards, other adapter standards available optionally
- separate pigtail and patchcord sections
- recommended pigtail length: 6 m, 2.0 mm or 2.4 mm cable diameter

### THE SET INCLUDES:

- cabinet with draw-out adapter frame
- installation and maintenance instructions
- installation kit

### ADDITIONAL EQUIPMENT:

- KS-24 splice trays zamawiane oddzielnie
- FC, ST adapter plates

### TECHNICAL SPECIFICATIONS:

	PS-4/72	PS-4/96	PS-4/144	PS-4/160	PS-4/192	PS-4/288	PS-4/320
number of lateral cable management sections	1				2		
number of splice trays KS-24	3	4	6	7	8	12	14
maximum number of splices	72	96	144	168	192	288	336
connector standard	E-2000/SC/LC (ST/FC)	E-2000/SC/LC (ST/FC)	E-2000/SC/LC (ST/FC)		E-2000/SC/LC (ST/FC)		
adapter capacity	72 (45)	160 (100)	160 (100)		320 (200)		
maximum diameter of input cable [mm]	18						
dimensions: width/height/depth [mm]	120/2200*/240	240/2000*/240			480/2200*/240		
recommended pigtail length [m], 2.0 or 2.4 mm cable diameter	6						
weight [kg]	35	66		75			
housing material/colour	steel sheet/RAL 7035						

\* 2600 mm height available upon request

### ORDERING:

PS-4/144/2.2/E2000-SC - Fibre Optic Distribution Frame, height 2.2 m, capacity: 144xE-2000, SC adapter positions

