

## PSH-2 OUTDOOR FIBRE OPTIC DISTRIBUTION

### FEATURES:

- wall mounted distribution box adapted to be mounted on the outside of the building
- for application in industrial environments with high dust level
- splitter installation
- separate splice and cross connect zones
- IP66 rated environmental protection
- possibility of installation on a plinth

### THE SET INCLUDES:

- adapter plate
- KS-24 splice trays
- cable glands DP-13, DP-16, DP-21
- cable ties and cable protective band
- installation and handling instructions
- installation kit

### ADDITIONAL EQUIPMENT:

- installation kit for Abloy lock in PSH fibre optic distribution box
- installation kit for Euro lock in PSH fibre optic distribution box

### TECHNICAL SPECIFICATIONS:

	PSH-2/12	PSH-2/24*	PSH-2/48	PSH-2/72	PSH-2/96	PSH-2/144
number of splice trays	2 x KS-24		4 x KS-24	6 x KS-24	8 x KS-24	12 x KS-24
maximum number of splices	24	24	48	72	96	144
adapter capacity	12	24	48	72	96	144
connector standard	E-2000, SC, FC, ST, LC Duplex					E-2000, SC, LC
recommended pigtail length [m], 2.0 mm cable diameter	2,5		3			4
number of outdoor cable entries	4		8			12
maximum diameter of input cable [mm]	18				21	26
dimensions: width/height/depth [mm]	300/400/200		400/500/200		400/600/230	800/600/300
weight [kg]	5,8		7,5	8	11	26
housing material/colour	glass fibre reinforced polyester/RAL 7035					
mechanical protection IK	IK 10					
environmental protection IP	IP66					

\* available with 48 adapter plate

### ORDERING:

PSH-2/96/E/SC - Outdoor Fibre Optic Distribution Box for 96 pigtails and E2000 or SC adapters



Outdoor Fibre Optic Distribution Box  
PSH-2/24



Outdoor Fibre Optic Distribution Box  
PSH-2/96



Outdoor Fibre Optic Distribution Box  
PSH-2/96