

PSM-19/120/3U MODULAR PATCH PANEL

FEATURES:

- up to 10 modules MPS-19/12/K or MPS-19/12
- quick and reliable fibre links configuration
- easy access for performing control and maintenance measurements
- MPS-19/0 module dedicated for port descriptions
- blank plates PZ-3U-8 (width 40 mm) to cover unused space in the panel
- installation in 19" racks with minimum depth of 300 mm, e.g. STP-19
- installation in 21" and/or 23" racks with the use of AD-19 adapters

THE SET INCLUDES:

- one module for port descriptions
- blank plate (optional)
- installation and handling instructions
- installation kit

TECHNICAL SPECIFICATIONS:

	PSM-19/120/3U
number of splice trays	max. 10 x KSQ
maximum number of splices	12 per module
adapter capacity	10 modules x 12 pcs = 120
connector standard	E-2000, SC, FC, ST
recommended pigtail length [m], 0.9 mm buffered fibre	1 - 1,5
dimensions: width/height/depth [mm]	483/132 (3U)/210
weight [kg]	4
number of modules	10
module type	MPS-19/12 or MPS-19/12/K
mounting brackets position	front

ORDERING:

PSM-19/120/3U - Modular Patch Panel, height 3U



*Modular Patch Panel
PSM-19/120/3U*