

PSM-19/144/3U MODULAR PATCH PANEL



Modular Patch Panel PSM-19/144/3U

FEATURES:

- capacity up to 12 modules MPS-19/12/W
- quick and reliable fibre links configuration
- easy access for performing control and maintenance measurements
- storage and organisation of outdoor cable loose tubes requires application of 19" Excess Cable Tray SZ-19L-1U
- blank plates PZ-3U-7 (width 35 mm) to cover unused space in the panel
- installation in 19" racks with minimum depth of 300 mm, e.g. STP-19
- installation in 21" and/or 23" racks with the use of AD-19 adapters

THE SET INCLUDES:

- cable ties and cable bands
- installation and handling instructions
- installation kit
- 19" Excess Cable Tray SZ-19L-1U (optional)
- blank plate (optional)

TECHNICAL SPECIFICATIONS:

| | PSM-19/144/3U |
|---|---------------------------|
| number of splice trays | max. 12 x KSQ |
| maximum number of splices | 12 per module |
| adapter capacity | 12 modules x 12 pcs = 144 |
| connector standard | E-2000, SC |
| recommended pigtail length [m], 0.9 mm buffered fibre | 1 - 1,5 |
| dimensions: width/height/depth [mm] | 483/132 (3U)/210 |
| weight [kg] | 4 |
| number of modules | 12 |
| module type | MPS-19/12/W |
| mounting brackets position | front |

ORDERING:

PSM-19/144/3U - Modular Patch Panel, height 3U